

High Frequency Silicon Nanowire Resonators for mass sensing

Laurent Durauffourg

CEA, LETI, MINATEC Campus, 17 rue des Martyrs, 38054 GRENOBLE Cedex 9, France

Abstract

For the last two decades, nanoelectromechanical systems (NEMS) such as silicon nanowires have exhibited incredible potential for both fundamental science and applications, providing new tools for studying quantum physics including electromechanics and optomechanics¹. Technological applications of NEMS are also emerging: these include integrated frequency clocks², logic switches³, mixer filters⁴, ultra-sensitive force detectors⁵ and mass sensors⁶. A variety of NEMS detection techniques, such as capacitive⁷, magnetomotive⁸, piezoresistive⁹ and field-emission¹⁰ transduction, have been proposed. However, interfacing NEMS and more specifically nanowires with the macro world remains a challenge. During the talk, an overview of the transduction schemes used for detecting tiny displacements of suspended nanowires will be presented. The presentation will briefly introduced VLSI-NEMS manufacturing with or without its co-integrated CMOS readout electronics. As an example, highly efficient in-plane motion detection based on suspended p⁺⁺-doped piezoresistive nanowires (the minimum section achieved is on the order of 40nmx30nm) will be presented. The smallest devices have been co-integrated with their readout electronics (on 40nm-Fully depleted technology¹¹) to arise the useful signal from the background with a fairly good Allan deviation lower than 1ppm. Results on high frequency vibrating silicon nanowires (the minimum section achieved is on the order of 40nmx30nm and 1µm-long) will also be presented. This last device can be transduced through piezoresistive technique and junction-less field-effect as well. Allan deviation of the same Si-NW has been measured with both schemes, and we obtained 20ppm for the FET detection and 3ppm for the PZR detection at room temperature and low pressure.

Finally, the talk will conclude on several emblematic applications related to mass sensing. Recent results on multi-gas detections and mass spectrometry with NEMS including silicon nanowires will be reported.

References

1. Kippenberg, T. J. & Vahala, K. J. Cavity optomechanics: back-action at the mesoscale. *Science* **321**, 1172–6 (2008).
2. Nguyen, C. T. C. MEMS technology for timing and frequency control. *IEEE transactions on ultrasonics, ferroelectrics, and frequency control* **54**, 251–70 (2007).
3. Loh, O. Y. & Espinosa, H. D. Nanoelectromechanical contact switches. *Nature nanotechnology* **7**, 283–95 (2012).
4. Wong, A. & Nguyen, C. T. Micromechanical Mixer-Filters (“Mixlers”). *Journal of Microelectromechanical Systems* **13**, 100–112 (2004).
5. Rugar, D., Budakian, R., Mamin, H. J. & Chui, B. W. Single spin detection by magnetic resonance force microscopy. *Nature* **430**, 329–32 (2004).
6. Chaste, J. *et al.* A nanomechanical mass sensor with yoctogram resolution. *Nature nanotechnology* **7**, 301–4 (2012).
7. Colinet, E. *et al.* Ultra-Sensitive Capacitive Detection Based on SGMOSFET Compatible With Front-End CMOS Process. *IEEE Journal of Solid-State Circuits* **44**, 1–11 (2009).
8. Feng, X. L., White, C. J., Hajimiri, a & Roukes, M. L. A self-sustaining ultrahigh-frequency nanoelectromechanical oscillator. *Nature nanotechnology* **3**, 342–6 (2008).
9. Li, M. O., Tang, H. X. & Roukes, M. L. Ultra-sensitive NEMS-based cantilevers for sensing , scanned probe and very high-frequency applications. *Nature Nanotechnology* **2**, 114–120 (2007).
10. Jensen, K., Kim, K. & Zettl, a. An atomic-resolution nanomechanical mass sensor. *Nature nanotechnology* **3**, 533–7 (2008).
11. Ollier, E. *et al.* Ultra-Scaled High-Frequency single-crystal Si NEMS resonators and their Front-End co-integration with CMOS for High Sensitivity Applications. in *MEMS2012* 1368–1371 (2012).