

Atom chip based guided atom interferometer for rotation sensing

Carlos L. Garrido Alzar¹, Wenhua Yan¹, Arnaud Landragin¹

¹LNE-SYRTE, CNRS, Observatoire de Paris, UPMC

61, avenue de l'Observatoire, 75014 Paris, France

Email: carlos.garrido@obspm.fr

In this work, the physical aspects as well as the experimental progress towards the realization of a rotation sensor using cold atoms magnetically guided on an atom chip are presented. The design and derivation of the magnetic guiding potential, the expected sensitivity, and the study of a highly efficient matter-wave beam splitter are in detail analyzed. This device is designed taking into account the stringent requirements of inertial navigation. Besides the usual constraints imposed on the physical dimensions and power consumption for the aforementioned application, we also investigate here the on-chip incorporation of keys elements needed in the realization of a cold atom interferometer. In particular, we discuss different strategies to overcome the fundamental limitations of guided¹ and free falling atom interferometer inertial sensors²: wire roughness induced decoherence, cloud fragmentation, interrogation time and quantum projection noise.

The working principle of this inertial sensor is based on a magnetic polarized cloud of cold ⁸⁷Rb atoms coherently split by a $\pi/2$ pulse that creates a superposition of two opposite wave-packet propagation modes. Both wave-packets will be constrained to propagate along a circular guide of a few millimeters diameter. At the output of the guide, the application of a second $\pi/2$ pulse produces an interference signal sensitive to rotation via the Sagnac effect, measured as an atom number imbalance. In Fig.1 we show the expected sensitivity of the designed device for an interrogation time of 1s and different launching velocities. For a typical launching velocity obtained via a Raman process ($v/v_{\text{recoil}} = 2$), the required guide radius is 500 μm and the sensitivity is $3 \times 10^{-8} \text{ rad.s}^{-1}/\sqrt{\text{Hz}}$ ($6 \times 10^{-3} \text{ deg/hr}/\sqrt{\text{Hz}}$) for $\sim 10^6$ atoms. Such a sensitivity is already close to the navigation grade bias stability requirement for a gyroscope which is on the order of 10^{-4} deg/hr .




Fig.1 : Expected sensitivity at the projection noise limit for 10^4 (blue) and 10^6 (red) atoms.

1 J.-B. Trebbia, C. L. Garrido Alzar, R. Cornelussen, C. I. Westbrook, and I. Bouchoule, “Roughness suppression via rapid current modulation on an atom chip”, Phys. Rev. Lett. 98, 263201 (2007)

2 B. Canuel, F. Leduc, D. Holleville, A. Gauguier, J. Fils, A. Virdis, A. Clairon, N. Dimarcq, Ch. J. Borde, and A. Landragin, “Six-axis inertial sensor using cold-atom interferometry”, Phys. Rev. Lett. 97, 010402 (2006)