

Phase-predictable tuning of single-frequency optical synthesizers

Thomas Puppe², Felix Rohde¹, Erik Benkler¹, Reinhard Unterreitmayer², Armin Zach²,

and Harald R. Telle¹

¹Physikalisch-Technische Bundesanstalt, Bundesallee 100, Braunschweig D-38116, Germany

²Toptica Photonics AG, Lochhamer Schlag 19, Graefelfing D-82166, Germany

Email: Thomas.Puppe@toptica.com

Single-frequency optical synthesizers (SFOS) provide an optical field with arbitrarily adjustable frequency and phase which is phase-coherently linked to a reference signal. Ideally, they combine the spectral resolution of narrow linewidth frequency stabilized continuous wave lasers with the broad spectral coverage of frequency combs¹ in a tunable fashion.

In previous implementations of SFOSs^{2,3,4}, a dedicated comb line order switching is needed when tuning over more than one repetition frequency of the employed mode-locked laser. This imposes technical overhead, leads to forbidden frequency gaps and limits the tuning agility of the SFOS.

Here, we present the characterization of a novel type of SFOS which relies on serrodyne-shifting⁵ of the frequency comb and subsequent selection of a single line. We investigate the tuning behavior of two identical SFOSs sharing a common frequency comb generator, by comparing the phases of their output signals as they are tuned while having a fixed frequency offset. We achieve phase-stable and cycle slip free frequency tuning over 28.1 GHz (>500 comb lines) with a short term rms phase deviation of 55 mrad (see Fig1). The tuning range using this approach can be extended to the full bandwidth of the frequency comb.




Fig. 1: Upper: Relative phase deviation of two SFOS during a triangular absolute frequency detuning across about 500 comb lines (28.1 GHz). Below: Independently frequency detuning of one of the SFOS monitored with an uncertainty of ± 100 MHz.

¹ R. Holzwarth, et al., “Optical frequency synthesizer for precision spectroscopy”, PRL 85 , p. 2264, 2000

² J. Jost, J. Hall, and J. Ye, “Continuously tunable, precise, single frequency optical signal generator”, Opt. Express 10, p. 515-520, 2002

³ T. R. Schibli, et al., “Displacement metrology with sub-pm resolution in air based on a fs-comb wavelength synthesizer”, Opt. Lett. 30, p. 5984-5993, 2005

⁴ V. Ahtee, M. Merimaa, and K. Nyholm, “Precision spectroscopy of acetylene transitions using an optical frequency synthesizer”, Opt. Express 17 , p. 2619-2621, 2009

⁵ E. Benkler, F. Rohde, and H. R. Telle, “Endless frequency shifting of optical frequency comb lines”, Opt. Exp. 21, p. 5793-5802, 2013